

# PROOPLE

Anti-slip and ground Safety Solutions

## ANTI-SLIP TO STICK

TBSAFE 65

## ANTI-SLIP TO STICK OR ADHESIVE

TBSAFE 21

TBSAFE 20S

RAMPE AMOVIBLE

## ANTI-SLIP ADHESIVE

SPEED GRIP

TBSAFE 21 AE1

TBSAFE 19

TBSAFE 16

TBSAFE 11R

TBSAFE 10




## COLOR

Colours not contractual.



BLACK

## PERFORMANCE TESTING\*



To deformation: 180% elongation before breakage.  
Abrasion: 640 mm<sup>3</sup>.  
Elongation: 24 kg/cm<sup>2</sup>.

## SPEED GRIP

Ultra-lightweight, self-adhesive anti-slip foam.

COMPOSITION: self-adhesive foam.

THICKNESS: 2 mm.

DENSITY: 0,24 g/cm<sup>3</sup>.

WEIGHT: 24 kg/cm<sup>2</sup>.

HARDNESS: 48 shore A.

APPLICATION: by adhesive, on any smooth surface such as polyester, painted or varnished wood, aluminium, stainless steel, ABS, epoxy carbon (test beforehand). Not suitable for rotomolded PE and PP.

MAINTENANCE: wash with water and conventional detergents on a regular basis. In factory and workshop, it is recommended to use industrial detergents with pH 9 and biodegradable.

STORAGE: in the original packaging, away from humidity. Handle at a temperature between +5°C and +30°C.

## APPLICATIONS :

- . Dinghies
- . Catamarans
- . Skiffs
- . Boat decks
- . Catamaran liston
- . Cockpit seat
- . Chainplate / spinnaker pole protection

## FORMATS

BOBINE  
self-adhesive

100 mm x 1,4 m

300 mm x 1,4 m

600 mm x 1,4 m

Tests performed by the following national laboratories: **GINGER CEBTP**  
**CEREMA**  
**LNE**

## ANTI-SLIP

1 rue du Coteau Moreau, 49290 Chalonnes-sur-Loire, FRANCE - Tél. +33 (0)2 44 10 85 29 - contact@proople.eu - www.proople.eu