

**ANTI-SLIP TACTILE SURFACE**

**PAD**

- RESIN PAD
- POLYMER PAD
- MINERAL PAD
- ALUMINIUM PAD

**STUD**

- ANTIQUE STEEL STUD
- STAINLESS STEEL STUD
- STAINLESS STEEL DOME

**ANTI-SLIP STAIR NOSING**

**ANTI-SLIP SURFACE  
ALUMINIUM PROFILE**

- FLAT PROFILE WITH INSERT
- SQUARE PROFILE WITH INSERT
- INSERT PROFILE WITH INSERT
- COMBO PROFILE WITH INSERT
- TILING PROFILE WITH INSERT

**RISER**

**ADHESIVE SURFACE  
ALUMINIUM PROFILE**

- PAINTED FLAT PROFILE
- POLYMER INSERTED FLAT PROFILE

**ANTI-SLIP GUIDING LINE**

**PAD**

- RESIN PAD
- POLYMER PAD
- MINERAL PAD

**POLYMER INSERTED  
ALUMINIUM PROFILE**



**MINERAL ANTI-SLIP GUIDING LINE  
BG3M / BG4M**

**PRODUCT BENEFITS**

The PROOPLE mineral anti-slip guiding line is UV and weather resistant. It is very resistant to high traffic and slipping, and is recommended for establishments receiving the public (Category 1) and for roadways. Its natural mineral appearance blends perfectly with historical landmarks. The guiding line is available with 3 or 4 grooves.

NF P-98352 STANDARD	INDOOR / OUTDOOR
MINERAL / MARBLE	HIGH TRAFFIC
UV RESISTANT	3 OR 4 GROOVES
PROOPLE® TEARDROP DESIGN	RAPID SURFACE AVAILABILITY FOR TRAFFIC
REACH COMPLIANT	

**PROOPLE RECOMMENDATION**

In a CSR approach, we recommend applying with adhesive, which eliminates health risks for operators and managing hazardous waste.

**METHODS OF INSTALLATION**

**Installation using adhesive**

- Time to install < 1 minute per pad
- Dry and clean surface with a particle size of < 2 mm
- Immediately available for traffic

**Installation using glue**

- Installation with a two-part methacrylate glue
- Traffic re-established < 1 hour

Please refer to our installation instructions.

**PERFORMANCE TESTING\***




**Resistance to slipping**

Tread SRT test > 0.50





**Resistance to fire and smoke**

Fire test  
Smoke test



**Product stability**

Indentation test  
Dimensional stability test



**Sizing and consistency**



**Adhesive strength**

FINAT peeling test (Thick adh.)

53,6 N / 25 MM

Tests carried out by the following French laboratories :

**GINGER CEBTP  
CEREMA  
LNE**

\*REGULATIONS | NF P98-352 Product Standard - Decrees of 8 December 2014 and 15 January 2007.

## ANTI-SLIP TACTILE SURFACE

### PAD

RESIN PAD  
POLYMER PAD  
MINERAL PAD  
ALUMINIUM PAD

### STUD

ANTIQUÉ STEEL STUD  
STAINLESS STEEL STUD  
STAINLESS STEEL DOME

## ANTI-SLIP STAIR NOSING

ANTI-SLIP SURFACE  
ALUMINIUM PROFILE

FLAT PROFILE WITH INSERT  
SQUARE PROFILE WITH INSERT  
INSERT PROFILE WITH INSERT  
COMBO PROFILE WITH INSERT  
TILING PROFILE WITH INSERT

## RISER

ADHESIVE SURFACE  
ALUMINIUM PROFILE

PAINTED FLAT PROFILE  
POLYMER INSERTED FLAT PROFILE

## ANTI-SLIP GUIDING LINE

### PAD

RESIN PAD  
POLYMER PAD  
MINERAL PAD

POLYMER INSERTED  
ALUMINIUM PROFILE

## DIMENSIONS

### BG3M: 3 canelures

- 820 x 162 mm

### BG4M: 4 canelures

- 820 x 222 mm

## COLOURS

IVORY	AGATE GREY
MELON YELLOW*	GREY TINT
CARMINE RED*	PALE BROWN*
OXYDE RED	WHITE
TRAFFIC BLUE*	BLACK
SIGNAL GREEN*	

\* COLOURS AVAILABLE IN SEPTEMBER 2017

## PACKAGING

Packaging < 15 Kg

NUMBER OF PRODUCTS	BG3M	BG4M
	6050 x 30	6050 x 50
PACK	6	6
EACH	2	2

## CONDITIONS FOR STORAGE AND USE

Store in original packaging, in a dry area.  
Install at between +5°C and +30°C.

## MAINTENANCE

Clean with water and regular cleaning products with a soft brush.

## TECHNICAL DIAGRAM

