

ANTI-SLIP TACTILE SURFACE

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD
- ALUMINIUM PAD

STUD

- ANTIQUÉ STEEL STUD
- STAINLESS STEEL STUD
- STAINLESS STEEL DOME

ANTI-SLIP STAIR NOSING

ANTI-SLIP SURFACE
ALUMINIUM PROFILE

- FLAT PROFILE WITH INSERT
- SQUARE PROFILE WITH INSERT
- INSERT PROFILE WITH INSERT
- COMBO PROFILE WITH INSERT
- TILING PROFILE WITH INSERT

RISER

ADHESIVE SURFACE
ALUMINIUM PROFILE

- PAINTED FLAT PROFILE
- POLYMER INSERTED FLAT PROFILE

ANTI-SLIP GUIDING LINE

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD

POLYMER INSERTED
ALUMINIUM PROFILE



PERFORMANCE TESTING*



Resistance to fire and smoke

Fire - Smoke test: Bfl-s1

COMPLIANT



Adhesive strength

AFERA 4001 peeling test

27 N / 25 MM

Tests carried out by the following French laboratories :

**GINGER CEBTP
CEREMA
LNE**

**ADHESIVE SURFACE RISER
C10P**

PRODUCT BENEFITS

The PROOPLE adhesive surface riser is UV and weather resistant, waterproof and easily cleaned. Its flexibility allows for it to be installed on all flat surfaces, both indoor and outdoor. It can rapidly equip a stairwell, and requires no special tools.

08/12/2014 REGULATION
POLYMER
UV RESISTANT
REACH COMPLIANT
10 CM WIDE

INDOOR / OUTDOOR
RAPID SURFACE AVAILABILITY
FOR TRAFFIC

PROOPLE RECOMMENDATION

Economical and simple to install, resists shocks and rubbing. We recommend the polymer riser for all flat surfaces.

METHODS OF INSTALLATION

Installation using adhesive

- Dry and clean surface with a grain size of < 1 mm
- Immediately available for traffic

Please refer to our installation instructions.

*REGULATIONS | Decrees of 8 December 2014.

ANTI-SLIP TACTILE SURFACE

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD
- ALUMINIUM PAD

STUD

- ANTIQUÉ STEEL STUD
- STAINLESS STEEL STUD
- STAINLESS STEEL DOME

ANTI-SLIP STAIR NOSING

ANTI-SLIP SURFACE
ALUMINIUM PROFILE

- FLAT PROFILE WITH INSERT
- SQUARE PROFILE WITH INSERT
- INSERT PROFILE WITH INSERT
- COMBO PROFILE WITH INSERT
- TILING PROFILE WITH INSERT

RISER

ADHESIVE SURFACE
ALUMINIUM PROFILE

- PAINTED FLAT PROFILE
- POLYMER INSERTED FLAT PROFILE

ANTI-SLIP GUIDING LINE

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD

POLYMER INSERTED
ALUMINIUM PROFILE

DIMENSIONS

C10P:

- 3005 x 100 mm

COLOURS

- MELON YELLOW
- GREY TINT
- WHITE
- BLACK

PACKAGING

Packaging < 15 Kg

| NUMBER OF PRODUCTS | C10P |
|--------------------|------------|
| | 3005 x 100 |
| EACH | 1 |

CONDITIONS FOR STORAGE AND USE

Store in original packaging, in a dry area.
Install at between +5°C and +30°C.

MAINTENANCE

Clean with water and regular cleaning products with a soft brush.

TECHNICAL DIAGRAM

