

**ANTI-SLIP TACTILE SURFACE**

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD
- ALUMINIUM PAD

**STUD**

- ANTIQUÉ STEEL STUD
- STAINLESS STEEL STUD**
- STAINLESS STEEL DOME

**ANTI-SLIP STAIR NOSING**

ANTI-SLIP SURFACE  
ALUMINIUM PROFILE

- FLAT PROFILE WITH INSERT
- SQUARE PROFILE WITH INSERT
- INSERT PROFILE WITH INSERT
- COMBO PROFILE WITH INSERT
- TILING PROFILE WITH INSERT

**RISER**

ADHESIVE SURFACE  
ALUMINIUM PROFILE

- PAINTED FLAT PROFILE
- POLYMER INSERTED FLAT PROFILE

**ANTI-SLIP GUIDING LINE**

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD

POLYMER INSERTED  
ALUMINIUM PROFILE




**PERFORMANCE TESTING\***



**Resistance to slipping**


Tread SRT test > 0.40  
AFPV test of dome > 0.45



**Resistance to fire and smoke**

Fire test  
Smoke test

MATERIAL COMPLIANT  
CLASSIFIED NON-FLAMMABLE




**Product stability**

Indentation test  
Dimensional stability test

COMPLIANT

COMPLIANT



**Sizing and consistency**

COMPLIANT

Tests carried out by the following French laboratories :

**GINGER CEBTP**  
**CEREMA**  
**LNE**

**TACTILE STAINLESS STEEL STUD CP5I**

**PRODUCT BENEFITS**

The PROOPLE stainless steel stud is adapted to high traffic in indoor installations. The design of its head gives it high resistance to slipping. Its shaft (8mm diameter and 22mm length) protects the head from shearing due to repeated shocks. Its marine-grade alloy (316L Stainless Steel) is recommended in applications requiring salt and snow resistance.

NF P-98351 STANDARD  
316L RECYCLABLE  
STAINLESS STEEL  
UV RESISTANT  
PROOPLE® GROOVED DESIGN

INDOOR / OUTDOOR  
HIGH TRAFFIC  
HIGH RESISTANCE TO SLIPPING  
RAPID SURFACE AVAILABILITY  
FOR TRAFFIC

**PROOPLE RECOMMENDATION**

By itself, the stud does not offer enough visual contrast with the surface. We recommend adapting the installation surface to create a standard contrast.

**METHODS OF INSTALLATION**

**Installation using mortar**

- All surface types excluding paving
- PROOPLE pre-drilled size
- Traffic re-established < 1 hour

Please refer to our installation instructions.

**ANTI-SLIP TACTILE SURFACE**

**PAD**

- RESIN PAD
- POLYMER PAD
- MINERAL PAD
- ALUMINIUM PAD

**STUD**

- ANTIQUÉ STEEL STUD
- STAINLESS STEEL STUD**
- STAINLESS STEEL DOME

**ANTI-SLIP STAIR NOSING**

**ANTI-SLIP SURFACE  
ALUMINIUM PROFILE**

- FLAT PROFILE WITH INSERT
- SQUARE PROFILE WITH INSERT
- INSERT PROFILE WITH INSERT
- COMBO PROFILE WITH INSERT
- TILING PROFILE WITH INSERT

**RISER**

**ADHESIVE SURFACE  
ALUMINIUM PROFILE**

- PAINTED FLAT PROFILE
- POLYMER INSERTED FLAT PROFILE

**ANTI-SLIP GUIDING LINE**

**PAD**

- RESIN PAD
- POLYMER PAD
- MINERAL PAD

**POLYMER INSERTED  
ALUMINIUM PROFILE**

**DIMENSIONS**

**Head**

- diameter 25 mm - thickness 5 mm

**Shaft**

- diameter 8 mm - length 22 mm

**COLOURS**

NATURAL MATTE STAINLESS STEEL

**PACKAGING**

Packaging < 15 Kg

NUMBER OF PRODUCTS	CP5I
PACKETS	75 PIECES

To cover an anti-slip tactile surface of 1 m in length, 2 packets are required for a 40 cm wide area, and 3 packets for a 60 cm wide area.

**CONDITIONS FOR STORAGE AND USE**

Store in original packaging, in a dry area.

**MAINTENANCE**

Clean with water and regular cleaning products with a soft brush.

**TECHNICAL DIAGRAM**

