

ANTI-SLIP TACTILE SURFACE

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD**
- ALUMINIUM PAD

STUD

- ANTIQUÉ STEEL STUD
- STAINLESS STEEL STUD
- STAINLESS STEEL DOME

ANTI-SLIP STAIR NOSING

ANTI-SLIP SURFACE
ALUMINIUM PROFILE

- FLAT PROFILE WITH INSERT
- SQUARE PROFILE WITH INSERT
- INSERT PROFILE WITH INSERT
- COMBO PROFILE WITH INSERT
- TILING PROFILE WITH INSERT

RISER

ADHESIVE SURFACE
ALUMINIUM PROFILE

- PAINTED FLAT PROFILE
- POLYMER INSERTED FLAT PROFILE

ANTI-SLIP GUIDING LINE

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD

POLYMER INSERTED
ALUMINIUM PROFILE



**TACTILE MINERAL PAD
DP4M**

PRODUCT BENEFITS

The PROOPLE mineral pad is UV and weather resistant. It is very resistant to high traffic and slipping, and is recommended for establishments receiving the public (Category 1) and for roadways. Its natural mineral appearance blends perfectly with historical landmarks.

- | | |
|--------------------------|--|
| NF P-98351 STANDARD | INDOOR / OUTDOOR |
| MINERAL / MARBLE | HIGH TRAFFIC |
| UV RESISTANT | HIGH RESISTANCE TO SLIPPING |
| PROOPLE® TEARDROP DESIGN | RAPID SURFACE AVAILABILITY FOR TRAFFIC |
| REACH COMPLIANT | |

PROOPLE RECOMMENDATION

In a CSR approach, we recommend applying with adhesive, which eliminates health risks for operators and managing hazardous waste.

METHODS OF INSTALLATION

Installation using adhesive

- Time to install < 1 minute per pad
- Dry and clean surface with a particle size of < 2 mm
- Immediately available for traffic

Installation using glue

- Installation with a two-part methacrylate glue
- All surface types excluding paving
- Traffic re-established < 1 hour

Please refer to our installation instructions.

PERFORMANCE TESTING*

Resistance to slipping
Tread SRT test > 0.40
AFPV test of dome > 0.45

0 N 0.69 1
0 N 0,49 1

Resistance to fire and smoke
Fire test
Smoke test

M4 M3 M2 M1
F4 F3 F2 F1 F0

Product stability
Indentation test
Dimensional stability test

COMPLIANT
COMPLIANT

Sizing and consistency

COMPLIANT

Adhesive strength
FINAT peeling test (Thick adh.)

53,6 N / 25 MM

Tests carried out by the following French laboratories :

ANTI-SLIP TACTILE SURFACE

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD**
- ALUMINIUM PAD

STUD

- ANTIQUÉ STEEL STUD
- STAINLESS STEEL STUD
- STAINLESS STEEL DOME

ANTI-SLIP STAIR NOSING

ANTI-SLIP SURFACE
ALUMINIUM PROFILE

- FLAT PROFILE WITH INSERT
- SQUARE PROFILE WITH INSERT
- INSERT PROFILE WITH INSERT
- COMBO PROFILE WITH INSERT
- TILING PROFILE WITH INSERT

RISER

ADHESIVE SURFACE
ALUMINIUM PROFILE

- PAINTED FLAT PROFILE
- POLYMER INSERTED FLAT PROFILE

ANTI-SLIP GUIDING LINE

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD

POLYMER INSERTED
ALUMINIUM PROFILE

DIMENSIONS

DP4M: Standard width in stairwells for establishments receiving the public

- 412 x 600 mm

COLOURS

IVORY*	AGATE GREY
MELON YELLOW	GREY TINT*
CARMINE RED	PALE BROWN*
OXYDE RED	WHITE
TRAFFIC BLUE*	BLACK
SIGNAL GREEN*	

* COLOURS AVAILABLE IN SEPTEMBER 2017

PACKAGING

Packaging < 15 Kg

NUMBER OF PRODUCTS	DP4M
	412 x 600
PACK	4
EACH	2

CONDITIONS FOR STORAGE AND USE

Store in original packaging, in a dry area.

Install at between +5°C and +30°C.

MAINTENANCE

Clean with water and regular cleaning products with a soft brush.

TECHNICAL DIAGRAM

