

**ANTI-SLIP TACTILE SURFACE**

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD
- ALUMINIUM PAD

STUD

- ANTIQUE STEEL STUD
- STAINLESS STEEL STUD
- STAINLESS STEEL DOME

**ANTI-SLIP STAIR NOSING**

ANTI-SLIP SURFACE  
ALUMINIUM PROFILE

- FLAT PROFILE WITH INSERT
- SQUARE PROFILE WITH INSERT
- INSERT PROFILE WITH INSERT
- COMBO PROFILE WITH INSERT**
- TILING PROFILE WITH INSERT

**RISER**

ADHESIVE SURFACE  
ALUMINIUM PROFILE

- PAINTED FLAT PROFILE
- POLYMER INSERTED FLAT PROFILE

**ANTI-SLIP GUIDING LINE**

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD

POLYMER INSERTED  
ALUMINIUM PROFILE



**ALUMINIUM MINERAL COMBO PROFILE WITH INSERT NO3AM / NO5AM**

**PRODUCT BENEFITS**

The PROOPLE combo profile aluminium mineral stair nosing is UV and weather resistant. It is very resistant to high traffic and slipping on wet surfaces, and is recommended for stairs in establishments receiving the public (Category 1) and for roadways. It brings together the nosing and the 10 cm polymer riser, with an anti-slip grooved edge, to better resist deformation. The contrasted anti-slip surface comes in 3 cm and 5 cm widths.

08/12/2014 REGULATION  
ALUMINIUM MINERAL  
UV RESISTANT  
REACH COMPLIANT  
3 CM OR 5 CM WIDTHS

INDOOR / OUTDOOR  
HIGH TRAFFIC  
HIGH RESISTANCE TO SLIPPING  
RAPID SURFACE AVAILABILITY  
FOR TRAFFIC

**PROOPLE RECOMMENDATION**

For stairwells with open stairs, or that are fragile or deteriorated, we recommend the combo profile for ease of installation and durability of the riser.

**METHODS OF INSTALLATION**

**Installed using screws**

- All stairway materials
- Immediately available for traffic

Please refer to our installation instructions.

**PERFORMANCE TESTING\***



**Resistance to slipping**

SRT Test



**Resistance to fire and smoke**

Fire - Smoke test: Bfl-s1

COMPLIANT

Tests carried out by the following French laboratories :

**GINGER CEBTP  
CEREMA  
LNE**

\*REGULATION | Decrees of 8 December 2014 and 15 January 2007.

## ANTI-SLIP TACTILE SURFACE

### PAD

RESIN PAD  
POLYMER PAD  
MINERAL PAD  
ALUMINIUM PAD

### STUD

ANTIQUÉ STEEL STUD  
STAINLESS STEEL STUD  
STAINLESS STEEL DOME

## ANTI-SLIP STAIR NOSING

### ANTI-SLIP SURFACE ALUMINIUM PROFILE

FLAT PROFILE WITH INSERT  
SQUARE PROFILE WITH INSERT  
INSERT PROFILE WITH INSERT  
**COMBO PROFILE WITH INSERT**  
TILING PROFILE WITH INSERT

### RISER

ADHESIVE SURFACE  
ALUMINIUM PROFILE

PAINTED FLAT PROFILE  
POLYMER INSERTED FLAT PROFILE

## ANTI-SLIP GUIDING LINE

### PAD

RESIN PAD  
POLYMER PAD  
MINERAL PAD

POLYMER INSERTED  
ALUMINIUM PROFILE

## DIMENSIONS

### NO3AM:

- 1150 x 30 mm
- 1500 x 30 mm
- 2300 x 30 mm

### NO5AM:

- 1150 x 50 mm
- 1500 x 50 mm
- 2300 x 50 mm

## COLOURS

ANTI-SLIP STAIR NOSING		RISER
IVORY	AGATE GREY	MELON YELLOW
MELON YELLOW	GREY TINT	GREY TINT
CARMINE RED*	PALE BROWN	WHITE
OXYDE RED	WHITE	BLACK
TRAFFIC BLUE*	BLACK	
SIGNAL GREEN*		

\* COLOURS AVAILABLE IN SEPTEMBER 2017

## PACKAGING

Packaging < 15 Kg

NUMBER OF PRODUCTS	NO3AM	NO5AM
	30	50
EACH	2	2

## CONDITIONS FOR STORAGE AND USE

Store in original packaging, in a dry area.  
Install at between +5°C and +30°C.

## MAINTENANCE

Clean with water and regular cleaning products with a soft brush.

## TECHNICAL DIAGRAM

