

ANTI-SLIP TACTILE SURFACE

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD
- ALUMINIUM PAD

STUD

- ANTIQUÉ STEEL STUD
- STAINLESS STEEL STUD
- STAINLESS STEEL DOME

ANTI-SLIP STAIR NOSING

ANTI-SLIP SURFACE
ALUMINIUM PROFILE

- FLAT PROFILE WITH INSERT
- SQUARE PROFILE WITH INSERT
- INSERT PROFILE WITH INSERT
- COMBO PROFILE WITH INSERT**
- TILING PROFILE WITH INSERT

RISER

ADHESIVE SURFACE
ALUMINIUM PROFILE

- PAINTED FLAT PROFILE
- POLYMER INSERTED FLAT PROFILE

ANTI-SLIP GUIDING LINE

PAD

- RESIN PAD
- POLYMER PAD
- MINERAL PAD

POLYMER INSERTED
ALUMINIUM PROFILE



ALUMINIUM POLYMER COMBO PROFILE WITH INSERT NO3AP / NO5AP

PRODUCT BENEFITS

The PROOPLE combo profile aluminium polymer stair nosing is UV and weather resistant. It is very resistant to high traffic and slipping on wet surfaces, and is recommended for all types of stairs in establishments receiving the public (Category 1) and for roadways. It brings together the nosing and the 10 cm polymer riser, with an anti-slip grooved edge, to better resist deformation. The contrasted anti-slip surface in widths of either 3 cm or 5 cm hides the screws when installed.

08/12/2014 REGULATION
ALUMINIUM POLYMER
UV RESISTANT
REACH COMPLIANT
3 CM OR 5 CM WIDTHS

08/12/2014 REGULATION
ALUMINIUM POLYMER
UV RESISTANT
REACH COMPLIANT
3 CM OR 5 CM WIDTHS

PROOPLE RECOMMENDATION

The anti-slip polymer band comes from PROOPLE's nautical experience, and is non-abrasive, for barefoot traffic. It is easily and economically replaced. We recommend it for humid environments.

METHODS OF INSTALLATION

Installed using screws

- All stairway materials
- Immediately available for traffic

Please refer to our installation instructions.

PERFORMANCE TESTING*



Resistance to slipping

SRT Test



Resistance to fire and smoke

Fire - Smoke test: Bfl-s1

COMPLIANT

Tests carried out by the following French laboratories :

**GINGER CEBTP
CEREMA
LNE**

*REGULATION | Decrees of 8 December 2014 and 15 January 2007.

ANTI-SLIP TACTILE SURFACE

PAD

RESIN PAD
POLYMER PAD
MINERAL PAD
ALUMINIUM PAD

STUD

ANTIQUÉ STEEL STUD
STAINLESS STEEL STUD
STAINLESS STEEL DOME

ANTI-SLIP STAIR NOSING

ANTI-SLIP SURFACE
ALUMINIUM PROFILE

FLAT PROFILE WITH INSERT
SQUARE PROFILE WITH INSERT
INSERT PROFILE WITH INSERT
COMBO PROFILE WITH INSERT
TILING PROFILE WITH INSERT

RISER

ADHESIVE SURFACE
ALUMINIUM PROFILE

PAINTED FLAT PROFILE
POLYMER INSERTED FLAT PROFILE

ANTI-SLIP GUIDING LINE

PAD

RESIN PAD
POLYMER PAD
MINERAL PAD

POLYMER INSERTED
ALUMINIUM PROFILE

DIMENSIONS

NO3AP:

- 1150 x 30 mm
- 1500 x 30 mm
- 2300 x 30 mm

NO5AP:

- 1150 x 50 mm
- 1500 x 50 mm
- 2300 x 50 mm

COLOURS

ANTI-SLIP STAIR NOSING		RISER
IVORY	AGATE GREY	MELON YELLOW
MELON YELLOW	GREY TINT	GREY TINT
CARMINE RED	PALE BROWN	WHITE
OXYDE RED*	WHITE	BLACK
TRAFFIC BLUE	BLACK	
SIGNAL GREEN		

* COLOURS AVAILABLE IN SEPTEMBER 2017

PACKAGING

Packaging < 15 Kg

NUMBER OF PRODUCTS	NO3AP	NO5AP
	30	50
EACH	2	2

CONDITIONS FOR STORAGE AND USE

Store in original packaging, in a dry area.
Install at between +5°C and +30°C.

MAINTENANCE

Clean with water and regular cleaning products with a soft brush.

TECHNICAL DIAGRAM

